

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 November 2006 (02.11.2006)

PCT

(10) International Publication Number
WO 2006/115465 A1

(51) International Patent Classification:
G11B 25/04 (2006.01) G11B 23/03 (2006.01)

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:
PCT/SG2005/000132

(22) International Filing Date: 26 April 2005 (26.04.2005)

(25) Filing Language: English

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(26) Publication Language: English

(71) Applicant (for all designated States except US): INNOVATIVE POLYMERS PTE. LTD. [SG/SG]; Block 201 #02-50, Woodlands Avenue 9, Singapore 738955 (SG).

Declarations under Rule 4.17:


- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- of inventorship (Rule 4.17(iv))

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TEST CARRIER FOR STORAGE DEVICES



WO 2006/115465 A1

(57) **Abstract:** A test carrier (10) for storage devices (38) comprising a carrier base (12); a slider tray (16) slidably mounted to the carrier base (12), the slider tray (16) having at least one aperture for receiving a storage device (38) therein; at least one storage device connector (20) connected to the carrier base (12); and a tester interface (22), where, when the slider tray (16) is in a first position, the storage device (38) can be received within the at least one aperture of the slider tray (16) and, when the slider tray (16) is in a second position, an interface of the storage device (38) mates with the storage device connector (20); appropriate circuitry contained in the carrier base (12) connecting the tester interface (22) and the storage device connector (20) thereafter allowing the storage device (38) to be tested via the tester interface (22).